# **SAFETY DATA SHEET**



Date of issue/Date of revision 1 May 2015 Version 3

Section 1. Identification	
Product name	: DULUX X-PERT I/F CEIL WHT
Product code	: 12170
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Industrial applications.
Use of the substance/ mixture	: Coating. Paints. Painting-related materials.
Uses advised against	: Not applicable.
Supplier	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)

# Section 2. Hazards identification

OSHA/HCS status	<ul> <li>This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).</li> </ul>
Classification of the substance or mixture	<ul> <li>CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1</li> <li>Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 28.5%</li> </ul>
<u>GHS label elements</u> Hazard pictograms	
Signal word Hazard statements	<ul> <li>Danger</li> <li>May cause cancer. Causes damage to organs through prolonged or repeated exposure.</li> </ul>

**United States** 

Page: 1/12

Product name DULUX X-PERT I/F CEIL WHT

### Section 2. Hazards identification

#### Precautionary statements

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention.
Storage	: Store locked up.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Supplemental label elements	<ul> <li>Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Emits toxic fumes when heated.</li> </ul>
Hazards not otherwise classified	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	1	Mixture
Product name	1	DULUX X-PERT I/F CEIL WHT

Ingredient name	%	CAS number
titanium dioxide	10 - 30	13463-67-7
Limestone	1 - 5	1317-65-3
Kaolin	1 - 5	1332-58-7
crystalline silica, respirable powder (<10 microns)	1 - 5	14808-60-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### Description of necessary first aid measures

Eye contact	<ul> <li>Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
	United States Page: 2/12

### Section 4. First aid measures

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

Potential acute health ef	fects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	<u>mptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Indication of immediate me	lical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
	United States Page: 3/12

Product name DULUX X-PERT I/F CEIL WHT

### Section 5. Fire-fighting measures

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	entainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Product name DULUX X-PERT I/F CEIL WHT

# Section 7. Handling and storage

Advice on general : occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before
	entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, : including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits	
titanium dioxide	OSHA PEL (United States, 2/2013).	
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust	
	ACGIH TLV (United States, 4/2014).	
	TWA: 10 mg/m <sup>3</sup> 8 hours.	
Limestone	OSHA PEL (United States, 2/2013).	
	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable	
	fraction	
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust	
Kaolin	ACGIH TLV (United States, 4/2014).	
	TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable	
	fraction	
	OSHA PEL (United States, 2/2013).	
	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable	
	fraction	
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust	
orvetalling cilica, reanizable novedar (<10 microna)	OSHA PEL Z3 (United States, 2/2013).	
crystalline silica, respirable powder (<10 microns)		
	TWA: 10 MG/M3 / (%SiO2+2) 8 hours. Form:	
	TWA: 250 MPPCF / (%SiO2+5) 8 hours.	
	Form: Respirable	
	ACGIH TLV (United States, 4/2014).	
	TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form:	
	Respirable.	
	OSHA PEL Z3 (United States).	
	TWA: 30 mg/m <sup>3</sup> Form: Total dust	
Key to abbreviation		
A = Acceptable Maximum Peak	S = Potential skin absorption	
ACGIH = American Conference of Governmental Industrial Hygienists.	SR = Respiratory sensitization SS = Skin sensitization	
C = Ceiling Limit F = Fume	STEL = Short term Exposure limit values	
IPEL = Internal Permissible Exposure Limit	TD = Total dust	
OSHA = Occupational Safety and Health Administration.	TLV = Threshold Limit Value	
	United States Page: 5/12	

Product name DULUX X-PERT I/F CEIL WHT

# Section 8. Exposure controls/personal protection

R = Respirable Z = OSHA 29C TWA = Time Weighted Average

= OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	<ul> <li>If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.</li> </ul>
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>es</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

		protection time of the gloves cannot be accurately estimated.
Body protection	1	Personal protective equipment for the body should be selected based on the task being
		performed and the risks involved and should be approved by a specialist before
		handling this product.
Other elvin protection		Appropriate featurer and any additional akin protection measures should be calested

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state	Liquid.	
Color	Not available.	
Odor	Not available.	
Odor threshold	Not available.	
рН	Not available.	
Melting point	Not available.	
Boiling point	>37.78°C (>100°F)	
Flash point	Closed cup: >93.33°C (>200°F)	
Material supports combustion.	Yes.	
Auto-ignition temperature	Not available.	
Decomposition temperature	Not available.	
Flammability (solid, gas)	Not available.	
Lower and upper explosive (flammable) limits	Not available.	
Evaporation rate	0.35 (butyl acetate = 1)	
Vapor pressure	2.3 kPa (17.5 mm Hg) [room temperature]	
Vapor density	Not available.	
Relative density	1.33	
Density(lbs / gal)	11.1	
Solubility	Insoluble in the following materials: cold water.	
Partition coefficient: n- octanol/water	Not available.	
Viscosity	Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)	
Volatility	<mark>ø</mark> 6% (v/v), 49.64% (w/w)	
% Solid. (w/w)	50.36	

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Product name DULUX X-PERT I/F CEIL WHT

### Section 10. Stability and reactivity

Hazardous decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity **Product/ingredient name** Result Dose Species **Exposure** titanium dioxide Rat LD50 Oral >10 g/kg Kaolin LD50 Oral >5000 mg/kg Rat **Conclusion/Summary** : There are no data available on the mixture itself. Irritation/Corrosion **Conclusion/Summary** Skin : There are no data available on the mixture itself. **Eyes** There are no data available on the mixture itself. : There are no data available on the mixture itself. Respiratory **Sensitization Conclusion/Summary** Skin : There are no data available on the mixture itself. Respiratory : There are no data available on the mixture itself. **Mutagenicity** : There are no data available on the mixture itself. **Conclusion/Summary Carcinogenicity Conclusion/Summary** : There are no data available on the mixture itself. **Classification Product/ingredient name OSHA IARC** NTP titanium dioxide 2B crystalline silica, respirable 1 Known to be a human carcinogen. powder (<10 microns)

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

#### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary** : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

**United States** 

Page: 9/12

Product name DULUX X-PERT I/F CEIL WHT

# Section 11. Toxicological information

powder (<10 microns)	Category 1
<ul> <li>Contains material which causes damage to the following of bone marrow.</li> <li>Contains material which may cause damage to the following upper respiratory tract, skin, stomach.</li> </ul>	
outes of exposure	
ects	
<ul> <li>No specific data.</li> <li>No specific data.</li> <li>No specific data.</li> <li>No specific data.</li> </ul>	
: There are no data available on the mixture itself. This prower which can cause lung cancer or silicosis. The risk of cancer and level of exposure to dust from sanding surfaces or missplashed in the eyes, the liquid may cause irritation and remay cause nausea, diarrhea and vomiting. This takes into delayed and immediate effects and also chronic effects of	duct contains crystalline silic cer depends on the duration st from spray applications. I eversible damage. Ingestion o account, where known, components from short-terr
: There are no data available on the mixture itself.	
There are no data available on the mixture itself.	
: There are no data available on the mixture itself.	
: There are no data available on the mixture itself.	
i <u>fects</u>	
	•
	<ul> <li>upper respiratory tract, skin, stomach.</li> <li>putes of exposure</li> <li>acts <ol> <li>No known significant effects or critical hazards.</li> </ol> </li> <li>In the specific data.</li> <li>No specific data.</li> <li>There are no data available on the mixture itself. This prowinking cause invitation and remay cause nusea, diarrhea and vomiting. This takes inter delayed and immediate effects and also chronic effects of and long-term exposure by oral, inhalation and dermal rou contact.</li> <li>There are no data available on the mixture itself.</li> <li>There are no data available on the mixture itself.</li> <li>There are no data available on the mixture itself.</li> <li>Causes damage to organs through prolonged or repeated May cause cancer. Risk of cancer depends on duration a No known significant effects or critical hazards.</li> <li>No known significant effects or critical hazards.</li> </ul>

### Section 11. Toxicological information

Numerical measures of toxicity

Acute toxicity estimates

Not available.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

# Section 13. Disposal considerations

1	The generation of waste should be avoided or minimized wherever possible. Disposal
	of this product, solutions and any by-products should at all times comply with the
	requirements of environmental protection and waste disposal legislation and any
	regional local authority requirements. Dispose of surplus and non-recyclable products
	via a licensed waste disposal contractor. Waste should not be disposed of untreated to
	the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
	Waste packaging should be recycled. Incineration or landfill should only be considered
	when recycling is not feasible. This material and its container must be disposed of in a
	safe way. Care should be taken when handling emptied containers that have not been
	cleaned or rinsed out. Empty containers or liners may retain some product residues.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains
	and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Product name DULUX X-PERT I/F CEIL WHT

## **14. Transport information**

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### Additional information

DOT	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# Section 15. Regulatory information

United States inventory (TSCA 8b	): All components are listed or exempted.
Australia inventory (AICS)	: At least one component is not listed.
Canada inventory ( DSL )	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory ( REACH )	: Please contact your supplier for information on the inventory status of this material.
Japan inventory (ENCS)	: At least one component is not listed.
Korea inventory (KECI)	: At least one component is not listed.
New Zealand ( NZIoC )	: At least one component is not listed.
Philippines inventory (PICCS)	: At least one component is not listed.
United States	
<u>SARA 302/304</u>	
SARA 304 RQ : N	Not applicable.
Composition/information on in	ngredients
No products were found.	
<u>SARA 311/312</u>	
Classification : [	Delayed (chronic) health hazard
Composition/information on in	ngredients

# Section 15. Regulatory information

Name		Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Manium dioxide crystalline silica, respirable powder (<10 microns)	No. No.	No. No.	No. No.	No. No.	Yes. Yes.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

#### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

# Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 \* Flammability : 1 Physical hazards : 0

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Ass	ociation (U.S.A.)		
Health : 1 Flamma	bility : 1 Instability : 0		
Date of previous issue	: 3/31/2015.		
Organization that prepared the MSDS	: EHS		
Key to abbreviations	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations		

#### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.