

SURFACE PREPARATION

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting.

- Mildew must be removed by washing affected area with a solution of 30% household bleach and 70% water. Rinse well.
- Scrub heavy chalk areas and overhead areas such as eaves with soap and water.
- Remove all loose and peeling paint and sand to smooth edges.
- Repair holes and cracks with filler suitable for the surface to be repaired.
- If wood exudes resin, scrape the excess and clean surface with alcohol or paint thinner.
- Sand all surfaces smooth, lightly sand glossy areas and sand weathered wood to a new wood appearance. Vacuum sanding residue.
Precaution: Dry sanding, flame cutting and/or welding of dry paint film will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

New concrete and masonry: must age at least 30 days and be thoroughly dry before painting.

Bare Wood: sand smooth.

Application

Ready-to-use product, do not thin.

Mix thoroughly before use.

Apply using brushes, rollers or spray equipment.

Suitable under latex or alkyd topcoats.

Application Conditions

Apply with good ventilation only when air and surface temperatures are above 40°F (4°C). For exterior applications do not apply if rain, snow or heavy dew is expected within 48 hours. Avoid painting in direct sunlight.

Tools

- Brush – synthetic bristles (nylon, polyester)
- Roller – 10–15 mm
- Spray (Airless equipment) – tip size: 0.013 to 0.019 in - Pressure: 2300 – 2700 psi

*Spray recommendations may vary from figures listed depending on equipment manufacturer

SYSTEM RECOMMENDATIONS

Two topcoats are recommended on all surfaces for better durability and appearance.

All recommended surfaces:

- Dulux Weatherguard 1535 – one coat to total surface.
- Appropriate Dulux topcoat

Note:

- Slight discolouration on redwood or cedar is normal. If discolouration is considerable, apply a second coat of Dulux Weatherguard 1535 or use Dulux Gripper

Clean-up

Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

Storage and Transportation

Keep product cool and dry.

DO NOT FREEZE

Disposal

Consult your municipality about proper disposal procedures in accordance with the laws and respect the environment or give leftover paint to someone who could use it: a neighbor or friend, a recreational service or a non-profit organization. Do not pour leftover product down the drain.

Safety Measures

Read the Material Safety Data Sheet. Avoid contact with eyes. Keep out of reach of children. Use only in well ventilated areas.

FIRST AID TREATMENT: If in contact with eyes, rinse thoroughly with clear water. If swallowed, do not induce vomiting. Call poison centre or physician immediately.

For product information call: 1-(800)-387-3663
www.dulux.ca