

GLIDDEN PRO INTERIOR LATEX PAINT 20071

Water based product, eggshell finish

Technical Data Sheet



Technical Specifications (21°C (70°F))

Solids by Volume – 35.6% (+/- 1%)
Solids by Weight – 55.3% (+/- 1%)

Volatile Organic Compounds (VOCs)*

According to ASTM D3960-05: < 50 g/L
Canadian regulation: < 150 g/L

Colour

White - (can be tinted to light pastel colours, maximum
1 oz. of universal colorant per litre)

Gloss Level

- Gloss @ 60°: 10%
- Sheen N/A

*Typical sheen @ 85°

Practical Coverage

380 - 420 sq. ft. per 3.78 litres
9 - 10 sq. metres per litre
(Actual coverage will vary depending on substrate
and application method.)

Resin Type

- Vinyl Acrylic

Viscosity* Ready to use (98 - 106 Krebs Units)

Flammability Non Flammable

Flash Point* N/A

Recommended Film Thickness*

- Wet: 4 mils
- Dry: 1.4 mils

Drying Time* @ 77°F/25°C - 50% Relative Humidity

**Drying & recoat times are dependent on temperature,
humidity, ventilation and film thickness*

Touch dry: 30 minutes

To recoat: 2 hours

Before cleaning: 7 – 10 days

Product Description

Glidden PRO Interior Eggshell 20071 is a professional quality product, formulated to meet the requirements of the commercial painter.

Glidden PRO Interior Eggshell 20071:

- Low sheen
- High hide
- Good Touch up

Intended Uses

- New and maintenance work
- Residential and Commercial sites
- Interior walls and ceilings
- Previously painted surfaces in good condition
- Properly primed surfaces: plaster, drywall, fibre boards, stucco, masonry, concrete and wood

*Technical Data Source: 20071

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labor or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages. *Dulux* is a registered trademark of AkzoNobel and is licensed to PPG Architectural Coatings Canada, Inc. for use in Canada only. The *Multi-Colored Swatches Design* is a trademark of PPG Architectural Finishes, Inc. *Glidden* is a registered trademark of the PPG Group of Companies. July 2014



Available at Dulux Paints Stores across Canada and Betonel-Dulux Stores in Québec

SURFACE PREPARATION

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting. Remove all surface contaminants by washing with an appropriate cleaner. Rinse thoroughly with water and allow to dry.

- Mildew must be removed by washing affected area with a solution of 30% household bleach and 70% water. Rinse well.
- Remove all loose and peeling paint and sand to smooth edges.
- Repair holes and cracks with filler suitable for the surface to be repaired.
- Sand all surfaces smooth and lightly sand glossy areas. Vacuum sanding residue.
Precaution: Dry sanding, flame cutting and/or welding of dry paint film will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

New Concrete, Masonry or Plaster: must age at least 30 days and be thoroughly dry before painting.

Bare Wood: sand smooth.

Application

Ready-to-use product, do not thin.

Mix thoroughly before use.

Apply using brushes, rollers or spray equipment.

Application Conditions

Apply with good ventilation only when air and surface temperatures are above 50°F (10°C)

Tools

- Brush – synthetic bristles (nylon, polyester)
- Lint free roller – 10-15 mm
- Spray (Airless equipment) – tip size:0.013 to 0.019 in - Pressure: 2300 – 2700 psi

*Spray recommendations may vary from figures listed depending on equipment manufacturer

Clean-up

Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

Storage and Transportation

Keep product cool and dry.

DO NOT FREEZE

SYSTEM RECOMMENDATIONS

Two topcoats are recommended on all surfaces for better durability and appearance.

Previously painted surfaces:

Surfaces in good condition

- No primer required
- Glidden PRO Latex Eggshell 20071

Repaired surfaces

- Glidden PRO Interior Latex Primer/Sealer 20051 – one coat (bare areas or total surface)
- Glidden PRO Latex Eggshell 20071

Aged alkyd surfaces

- Dulux Gripper 60000 – one coat over total surface
- Glidden PRO Latex Eggshell 20071

New surfaces:

Drywall, plaster, fibre board, concrete, stucco or masonry:

- Glidden PRO Interior Latex Primer/Sealer 20051 - one coat to total surface
- Glidden PRO Latex Eggshell 20071

Wood:

- Dulux Gripper 60000 – one coat over total surface
- Glidden PRO Latex Eggshell 20071

Disposal

Consult your municipality about proper disposal procedures in accordance with the laws and respect the environment or give leftover paint to someone who could use it: a neighbor or friend, a recreational service or a non-profit organization. Do not pour leftover product down the drain.

Safety Measures

Read the Material Safety Data Sheet. Avoid contact with eyes. Keep out of reach of children. Use only in well ventilated areas.

FIRST AID TREATMENT: If in contact with eyes, rinse thoroughly with clear water. If swallowed, do not induce vomiting. Call poison centre or physician immediately.

For product information call: 1-(800)-387-3663
www.dulux.ca