DULUX X-PERT
INTERIOR ACRYLIC LATEX PAINT
14010

Water based product, eggshell finish

Technical Data Sheet

Technical Specifications (21°C (70°F))

Solids by Volume – 36% (+/- 1%)
Solids by Weight – 54% (+/- 1%)

Volatile Organic Compounds (VOCs)*

According to ASTM D3960-05: < 150 g/L
Canadian regulation: < 150 g/L

Colour

White, medium and ultra deep bases

Gloss Level **Eggshell finish**

- Gloss @ 60°: 5 – 10%
- Sheen @ 85°: 10 – 35%

Practical Coverage

380 - 420 sq. ft. per 3.78 litres
9 - 10 sq. metres per litre
(Actual coverage will vary depending on substrate and application method.)

Resin Type

- Vinyl Acrylic

Viscosity* Ready to use (95 - 105 Krebs Units)

Flammability Non Flammable

Flash Point* N/A

Recommended Film Thickness*

- Wet: 4 mils
- Dry: 1.4 mils

Drying Time* @ 77°F/25°C - 50% Relative Humidity

**Drying & recoat times are dependent on temperature, humidity, ventilation and film thickness*

Touch dry:	30 minutes
To recoat:	4 hours
Before cleaning:	7 – 10 days

*Technical Data Source: 14010

Product Description

Dulux X-pert Interior Eggshell 14010 is a premium product, formulated to provide great coverage, high hide and excellent adhesion for any project. Its outstanding flow and application properties result in a smooth uniform finish

Dulux X-pert Interior Eggshell 14010:

- Easy application
- Good touch up

Intended Uses

- New and maintenance work
- Residential and Commercial sites
- Walls, doors and trim of any room
- Properly primed surfaces: plaster, drywall, fibre boards, stucco, masonry, concrete and wood

Certifications - *As of October 2013*

Approved to:

- MPI – Category #44, Interior Latex Eggshell (MPI Gloss Level 2)

Complies with:
LEED® Canada - CI (2006) and NC & CS (2009)

GUARANTEE: PPG Architectural Coatings Canada Inc. guarantees performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other guarantee, expressed or implied, statutory or otherwise is given. We shall not be responsible for any indirect, consequential or other damages.
Edition of October 2013

Available at Dulux Paints Stores across Canada and Betonel-Dulux Stores in Québec

SURFACE PREPARATION

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting. Remove all surface contaminants by washing with an appropriate cleaner. Rinse thoroughly with water and allow to dry.

- Mildew must be removed by washing affected area with a solution of 30% household bleach and 70% water. Rinse well.
- Remove all loose and peeling paint and sand to smooth edges.
- Repair holes and cracks with filler suitable for the surface to be repaired.
- Sand all surfaces smooth and lightly sand glossy areas. Vacuum sanding residue. *Precaution:* Dry sanding, flame cutting and/or welding of dry paint film will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

New Concrete, Masonry or Plaster: must age at least 30 days and be thoroughly dry before painting.
Bare Wood: sand smooth.

Application

Ready-to-use product, do not thin.
Mix thoroughly before use.
Apply using brushes, rollers or spray equipment.

Application Conditions
Apply with good ventilation only when air and surface temperatures are above 50°F (10°C)
Tools

- Brush – synthetic bristles (nylon, polyester)
- Lint free roller – 10-15 mm
- Spray (Airless equipment) – tip size:0.013 to 0.019 in - Pressure: 2300 – 2700 psi

*Spray recommendations may vary from figures listed depending on equipment manufacturer

Clean-up

Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

Storage and Transportation

Keep product cool and dry.
DO NOT FREEZE

SYSTEM RECOMMENDATIONS

Two topcoats are recommended on all surfaces for better durability and appearance.

Previously painted surfaces:
Surfaces in good condition
• No primer required
• Dulux X-pert Eggshell 14010
Repaired surfaces
• Dulux X-pert Eggshell 14010 may be used self-priming, as a primer coat under itself - one coat (bare areas or total surface)
• Dulux X-pert Eggshell 14010
Aged alkyd surfaces
• Gripper 250 – one coat over total surface
• Dulux X-pert Eggshell 14010
New surfaces:
Drywall, plaster, fibre board, concrete, stucco or masonry:
• Dulux X-pert Interior Latex Primer/Sealer 11000 – one coat over total surface
• Dulux X-pert Eggshell 14010
Wood:
• Gripper 250– one coat over total surface
• Dulux X-pert Eggshell 14010
Vivid, brilliant and deep colours:
• Ultra Latex Accent Basecoat – one coat to total surface.
• Dulux X-pert Eggshell 14010 – additional coat may be required

Disposal

Consult your municipality about proper disposal procedures in accordance with the laws and respect the environment or give leftover paint to someone who could use it: a neighbor or friend, a recreational service or a non-profit organization. Do not pour leftover product down the drain.

Safety Measures

Read the Material Safety Data Sheet. Avoid contact with eyes. Keep out of reach of children. Use only in well ventilated areas.
FIRST AID TREATMENT: If in contact with eyes, rinse thoroughly with clear water. If swallowed, do not induce vomiting. Call poison centre or physician immediately.

For product information call: 1-(800)-387-3663
www.dulux.ca

This technical data sheet, No. 14010, replaces all earlier versions. Edition of October 2013