

DULUX® VENETIAN SILK™ INTERIOR PAINT 84000/85000

Water based product, matt finish

Technical Data Sheet



Technical Specifications (21°C (70°F))

Solids by Volume:	34% (± 1%)
Solids by Weight:	49% (± 1%)

Volatile Organic Compounds (VOCs)*

According to ASTM D3960-05:	< 50 g/L
Canadian regulation:	< 100 g/L

Colour

Base 1 (84000) may be applied without tinting.
Base 2 (85000) must be tinted before use.

Gloss Level

- Gloss @ 60°: 0 – 5%
- Sheen @ 85°: 0 – 5%

Matt finish

Practical Coverage

300 - 400 sq. ft. per 3.78 litres in two coats
7 - 9 sq. metres per litre in two coats

(Coverage figures do not include loss due to surface irregularities and porosity, or material loss due to application method or mixing.)

It will take two coats of the topcoat over the basecoat to achieve the look of Dulux Venetian Silk.

Resin Type

- Latex

Viscosity*: 105 - 115 Krebs Units

Flammability	Non Flammable
Flash Point*	Not applicable

Recommended Film Thickness*

- Wet: 4.0 mils (102 µm)
- Dry: 1.4 mils (35 µm)

Drying Time* @ 77°F/25°C - 50% Relative Humidity

* Drying & recoat times are dependent on temperature, humidity, ventilation and film thickness

Touch dry:	2 hours
To recoat:	4 hours
Before cleaning:	30 days

*Technical Data Source: 84000

Product Description

DULUX VENETIAN SILK interior coating is designed to produce a soft, luxurious finish with a silky layered warmth. By layering it over a basecoat it adds depth and texture creating an atmosphere of old-world charm. As the ambient light changes in any room, the appearance of this unique finish continues to evolve.

- A soft, luxurious finish with a silky layered warmth.
- Dulux Venetian Silk is best suited to low-traffic areas.
- Inadvisable use on ceilings or textured walls.

Intended Uses

The Dulux Venetian Silk finish is created by 2 applications of Dulux Venetian Silk over Dulux DIAMOND™ eggshell paint.

Allow Dulux DIAMOND paint to dry overnight before applying the Dulux Venetian Silk topcoat.

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labor or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages.

Dulux is registered trademarks of AkzoNobel and Diamond is a trademark of AkzoNobel, and are licensed to PPG Architectural Coatings Canada, Inc. for use in Canada only. The Multi-Coloured Swatches Design is a registered trademark of PPG Architectural Finishes, Inc.



Available at Dulux Paints Stores across Canada and Bétonel-Dulux Stores in Québec

September 2016

SURFACE PREPARATION

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before application.

Remove all surface contaminants by washing with an appropriate cleaner.

Rinse thoroughly with water and allow to dry.

► Mildew must be removed by washing affected area with a solution of 30% household bleach and 70% water. Rinse well.

► Remove all loose and peeling paint and sand to smooth edges.

► Repair any imperfections on the wall such as nail holes, cracks, chip, nicks with filler suitable for the surface to be repaired.

► Sand all surfaces smooth and lightly sand glossy areas. Clean up carefully sanding residue with a HEPA vacuum and a wet mop. Spot prime with **Dulux Diamond** eggshell.

Precaution: Dry sanding will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Previously painted latex surfaces: spot prime repairs or any bare areas or total surface where necessary.

Application

Do not thin, product must be tinted.

The Dulux Venetian Silk topcoat is a thick, heavy-bodied product and should be shaken for 2 minutes before tinting.

After tinting, shake for an additional 4 minutes.

Put painter's tape around any adjacent surfaces.

Apply two coats of the appropriate Dulux Diamond eggshell complementary colour.

Allow final basecoat to dry overnight before applying the *Dulux Venetian Silk* topcoat finish. Stir paint thoroughly before use.

The same person should apply Dulux Venetian Silk to all walls for a consistent appearance throughout the room.

Apply by using the appropriate spreading tool or 9 in Trowel. Scoop enough *Venetian Silk* to cover about 1 cm (½ in.) of the edge of the application tool. Starting in an upper corner, spread Venetian Silk onto the wall, sweeping across the wall in a sideways arch. Always sweep in the same direction. Continue spreading until a smooth, thin coat covers an irregularly shaped area of 1 - 2 sq. ft.

Always blend into previously coated areas, fanning across and down until the entire wall is covered with a smooth, thin coat.

Apply to narrow spaces by moving application tool side to side.

When applying to adjoining walls easily wrap around corners by ending in the corner crease and continuing onto the next wall.

Allow to dry 4 hours then repeat steps to apply a second coat.

Applying second coat too soon may cause the first coat to gum up during application.

After second coat is applied, remove tape and allow wall to dry overnight. **Provide adequate ventilation.** Observe drying time between coats. Low temperatures or high humidity will affect drying time.

Application Conditions

Apply with good ventilation only when air and surface temperatures are above 50°F (10°C)

Tools

- Appropriate spreading tool
- 9 in Trowel

SYSTEM RECOMMENDATIONS

Previously painted surfaces:

Surfaces in good condition

- Dulux Diamond Eggshell 15110
- Dulux Venetian Silk 84000 or 85000 (2 coats)

Repaired surfaces

- Dulux Diamond Eggshell 15110
- Dulux Venetian Silk 84000 or 85000 (2 coats)

Aged alkyd surfaces

- Dulux X-pert Waterborne Alkyd Primer 23010 or Dulux Gripper 60000 – one coat over total surface
- Dulux Diamond Eggshell 15110
- Dulux Venetian Silk 84000 or 85000 (2 coats)

New surfaces:

Drywall, plaster, fibre board, concrete, wood, stucco or masonry:

- Dulux Diamond Eggshell 15110
- Dulux Venetian Silk 84000 or 85000 (2 coats)

Clean-up

Remove as much product quantity as possible and clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

Storage and Transportation

Keep product cool and dry.

DO NOT FREEZE

Disposal

Consult your municipality about proper disposal procedures in accordance with the laws and respect the environment or give leftover paint to someone who could use it: a neighbor or friend, a recreational service or a non-profit organization. Do not pour leftover product down the drain.

Safety Measures

Read the Material Safety Data Sheet. Keep container tightly closed and sealed until ready for use. **MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION.** Avoid breathing vapours, spray or mists. Avoid contact with skin and eyes. Wear protective gloves/clothing and eye/face protection. Keep out of reach of children. For workplace use, an MSDS is available from your retailer or by calling 1-800-463-7426.

FIRST AID TREATMENT: If swallowed, call a Poison Control Centre or doctor immediately. If in eyes or on skin, rinse well with water. If breathed in, move person to fresh air. Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications.

For product information call: 1-(800)-387-3663

www.venetiansilk.ca

www.dulux.ca